



## RTC Rental D4800

RTC D4800 non-cycling, direct-expansion refrigeration dryer, suitable for a flow of 80m<sup>3</sup>/min at 7 bar(g), equipped with an integrated control system.

- Cycling direct operating refrigeration dryer
- Complete package with built-in controls and automatic drain system
- Electric driven, highly efficient hermetic compressor

### Technical Data

|                       |                                                         |
|-----------------------|---------------------------------------------------------|
| Max. capacity         | 80m <sup>3</sup> /min (4800m <sup>3</sup> /h – 2824cfm) |
| Max. working pressure | 11 Bar(g) – (155 PSI (g))                               |
| Min/Max. inlet temp.  | +5 to +40°C                                             |
| Min/Max ambient       | +5 to +46°C                                             |
| Pressure dew point    | +2 to +10°C                                             |
| Discharge connection  | DN150-PN16 *                                            |
| Voltage               | 400 V, 3 Ph, 50 Hz                                      |
| Absorbed power        | 10.3 kW                                                 |
| Absorbed current      | 18.6 A                                                  |
| Gross weight          | 1400 kg                                                 |
| Dimensions            | 1500 × 1510 × 1570mm                                    |
| Sound Pressure        | <70db(A) (EN ISO 2151:2004)                             |

\* Other connection on request

**To experience RTC Group for yourself please call +316 53 85 82 17  
or visit us at [www.oilfree-air.eu](http://www.oilfree-air.eu) to discuss your needs.**