



## RTC Rental DB24

RTC DB24 regenerating desiccant dryer, suitable for a flow of 28m<sup>3</sup>/min at 11 Bar(g), with integrated control system.

- External-heat regeneration system
- No loss of compressed air for regeneration or cooling
- Pressure drop lower than 0.1 bar at full capacity
- Sophisticated PLC control and communication unit
- Parallel drying phase for steady dewpoint performance

### Technical Data

|                       |                                                        |
|-----------------------|--------------------------------------------------------|
| Max. capacity         | 28m <sup>3</sup> /min (1675m <sup>3</sup> /h – 990cfm) |
| Max. working pressure | 11 Bar(g) – (155 PSI (g))                              |
| Min/Max. inlet temp.  | +5 to +40°C                                            |
| Pressure dew point    | -20 to -40°C                                           |
| Discharge connection  | DN80-PN16                                              |
| Voltage               | 400 V, 3 Ph, 50 Hz                                     |
| Absorbed power        | 20 kW                                                  |
| Gross weight          | 2200 kg                                                |
| Dimensions            | 2300 × 1750 × 2950mm                                   |
| Sound Pressure        | 72db(A) (EN ISO 2151:2004)                             |
| during blow-off       | 80db(A)                                                |

**To experience RTC Group for yourself please call +316 53 85 82 17 or visit us at [www.oilfree-air.eu](http://www.oilfree-air.eu) to discuss your needs.**