



RTC Rental WS2190S

RTC WS2190S 2-stage 100% oil-free booster compressor. Electric drive delivering 45m³/min (1590cfm) at 40 Bar(g) (560psi) of class zero quality air.

- Complete tested package with built-in lubrication and cooling systems
- Belt driven motor
- Complete control, protection and diagnostic system
- Integral water-cooled inter- and aftercooler with single point flanged connections for air and water
- Fully containerised package with discharge air buffer tank (42 Bar(g))

Technical Data

Max. capacity	45m ³ /min (2700m ³ /h – 1590cfm)
Inlet pressure	10 Bar(g) – (140 PSI (g))
Inlet connection	3" Camlock Male
Discharge pressure	40 Bar(g) – (560 PSI (g))
Safety valve setting	42 Bar(g) – (588 PSI (g))
Discharge connection	G2" (80 Bar)
Cooling	Water cooling
Cooling pressure	min. 3 Bar – max. 5 Bar
Cooling flow	266 l/min
Cooling connection	3" Camlock Male (IN / OUT)
Voltage	400 V, 50 Hz, 3 Ph
Rated speed comp	890 rpm
Auxiliary power	400 V, 3 Ph, 50 Hz, 16 A
Gross weight	11,500 kg
Dimensions	6100 × 2440 × 2590mm
Sound Pressure	<80db(A) (EN ISO 2151:2004)

**To experience RTC Group for yourself please call +316 53 85 82 17
or visit us at www.oilfree-air.eu to discuss your needs.**